

HUNT Dimming has been a quality and industry-respected manufacturer of commercial-grade Wallbox Dimmers and Dimming Systems since 1960.

HUNT manufactures solid-state, U.L. Listed dimmers to control Incandescent, Fluorescent (both electronic and magnetic), Low-Voltage, Neon and Cold Cathode light sources. Controls are also available for various Fan-Speed and Motor Control applications.

HUNT Architectural Wallbox Dimmers give you:

- Products dim electronic T8's and CFL's
- Both 0 to 10 Volt and Phase-Control technologies
- Controls for low or high-power applications
- Over 200 stock items that ship same day
- The most extensive line of 240/277 Volt controls available
- Custom 277 Volt and 50 Hz controls
- Small lot OEM capabilities
- ISO 9000 products
- Aggressive Distributor Stock program with low minimum stock level

HUNT's <u>Architectural Dimming Systems</u> are easy-to-understand, simple-to-use, and economical. Many applications require only a few simple presets or slides. Systems that most everyone understands.

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.







0 to 10 Volt D.C. Controls for Dimmable Electronic Fluorescent Ballasts

HUNT Dimming has a full line of 0 to 10 Volt D.C. controls for use with dimmable electronic fluorescent ballasts. These dimmers provide linear lighting control from 100% to 5% of rated lumen output and are available for both 120V and 277V applications. HUNT's Eclipsis series model PS-010 specification-grade, preset slide wallbox dimmer is for use in low-amperage applications controlling up to 40 T8 lamps. The model FD-010 modular system incorporates a unique wall mounted, single-point-of-control preset slide unit with a remote-mounted module for high-amperage applications controlling up to 100 T8 lamps. HUNT's 0 to 10 Volt dimming controls support ballasts manufactured by Advance, Motorola, Prescolite, ESI, MagneTek/Universal, GE, and Osram/Sylvania.

Hunt Product Code	Model Number	Description	NSN			
Wall Box	Wall Box					
71510	PS-010-IV-12OV	Preset slide, controls 32 T8 lamps				
71511	PS-010-WH-12OV	Preset slide, controls 32 T8 lamps				
71512	PS-010-3W-IV-12OV	Preset slide, controls 32 T8 lamps				
71513	PS-010-3W-WH-12OV	Preset slide, controls 32 T8 lamps				
71530	PS-010-IV-277V	Preset slide, controls 32 T8 lamps				
71531	PS-010-WH-277V	Preset slide, controls 32 T8 lamps				
71632	PS-010-3W-IV-277V	Preset slide, controls 32 T8 lamps				
71533	PS-010-3W-WH-277V	Preset slide, controls 32 T8 lamps				
MINISYS	TEM					
71355	PS-IFC-010-IV-120/277V	Preset slide, controls FD-010				
71356	PS-IFC-010-WH-120/277V	Preset slide, controls FD-010				
71357	PS-IFC-010-3W-IV-120/277V	Preset slide, controls FD-010				
71358	PS-IFC-010-3W-WH-120/277V	Preset slide, controls FD-010				
71516	FD-010-12OV	Remote mounted unit, controls 100 T8 Lamps.				
71517	FD-010-277V	Remote mounted unit, controls 100 T8 Lamps				
71 XX	Custom Color or Configuration Available	Call DSCP Lighting Team for information				

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Phase-Control Dimmers for Dimmable Electronic Fluorescent Ballasts

HUNT Dimming has a full line of Phase-Control (Two-Wire) dimmers for use with dimmable electronic fluorescent ballasts. These dimmers provide continuous, flicker-free dimming control from 100% to 5% of rated lumen output and are available for both 120V and 277V applications. HUNT's Eclipsis series model PS-600 Phase-Control specification-grade, preset slide wallbox dimmer is for use in low-wattage applications controlling up to 20 T8 lamps. The FD series Phase-Control modular systems incorporate a unique wall mounted, single-point-of-control preset slide unit with one or several remote-mounted modules for high-wattage applications controlling up to 800 T8 lamps. HUNT's Phase-Control dimming products support ballasts manufactured by Advance.



	P	S-600 Mark X series				
Hunt Product Code	Model Number	Description	NSN			
120 Volt Low Power ap	plications for up to 16 T8's or 2	20 CFL's				
65500	PS-600-IV Mark X 120V	Preset slide, Controls 600 Watt Maximum, Ivory				
65501	65501 PS-600-WH Mark X 120V Preset slide, Controls 600 Watt Maximum , White					
65510	PS-600-3W-IV Mark X 120V	Preset slide, Controls 600 Watt Maximum, 3 Way, Ivory				
65511	PS-600-3W-WH Mark X 120V	Preset slide,Controls 600 Watt Maximum, 3 Wayems,White				
277 Volt Low Power ap	plications for up to 16 T8's or 2	20 CFL's				
65520	PS-600-IV Mark X 277V	Preset slide for Modular Mark X systems, Ivory				
65521	PS-600-WH Mark X 277V	Preset slide for Modular Mark X systems,White				
65530	PS-600-3W-IV Mark X 277V	Preset slide 3 Way for Modular Mark X systems, Ivory				
65531	PS-600-3W-WH Mark X 277V	Preset slide 3 Way for Modular Mark X systems,White				
	FD Mark X	Series requires a PS-IFC together with a FD power unit				
120 or 277 Volt applica	tions for up to 8 T8's and CFL	's				
71320	PS-IFC-IV Mark X	Preset slide for Modular Mark X systems, Ivory				
71321	PS-IFC-WH Mark X	Preset slide for Modular Mark X systems,White				
71330	PS-IFC-3W-IV Mark X	Preset slide 3 Way for Modular Mark X systems, Ivory				
71331	PS-IFC-3W-WH Mark X	Preset slide 3 Way for Modular Mark X systems,White				
Fluorescent - 120 Volt	T8's and CFL's					
71340	FD-30 MASTER Mark X	Master unit for up to 3kw				
71341	FD-30-S SLAVE Mark X	Slave unit for up to 3kw				
71350	FD-20 MASTER Mark X	Master unit for up to 2kw				
71351	FD-20-S SLAVE Mark X	Slave unit for up to 2kw				
Fluorescent - 277 Volt	T8's and CFL's	<u> </u>				
71360	FD-27 MASTER Mark X	Master unit for up to 2kw				
71361	FD-27-S SLAVE Mark X	Slave unit for up to 2kw				

*** "Mark X" is a Registered Trade Mark for Advance Trasnformer Line Voltage Dimming Ballasts *** HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Luminist Series

- Applications: Incandescent, Fluorescent & Low Voltage.
- Preset slide control.
- Easy-to-operate, smooth-sliding linear control & switch.
- Snap-on plastic cover holds slide securely in place.
- No exposed fins or hardware.
- Standard designer-style.
- Limited two-year warranty





Incandescent - 120 Volt applications

Hunt Product Code	M odel N um ber	Description 120 Volt applications	U n it Pack Master Carton	U nit W e ight	NSN
68100	D A P -8 -IV	800 watts, preset slide, ivory	1 0	14 oz	
68101	D A P -8 -W H	800 watts, preset slide, white	1 0	14 oz	
68110	D A P -8 -3 W -IV	800 watts, preset slide, 3-way, ivory	2	14 oz	
68111	D A P -8 -3 W -W H	800 watts, preset slide, 3-way, white	2	14 oz	
68120	D A P -1 0 - IV	1000 watts, preset slide, ivory	5	15 oz	
68121	D A P -1 0 -W H	1000 watts, preset slide, white	5	15 oz	
68130	D A P -1 0 -3 W -IV	1000 watts, preset slide, 3-way, ivory	2	15 oz	
68131	D A P -1 0 -3 W -W H	1000 watts, preset slide, 3-way, white	2	15 oz	
68140	D A P -1 5 - IV	1500 watts, preset slide, ivory	2	18 oz	
68141	D A P -15-W H	1500 watts, preset slide, white	2	18 oz	
68150	D A P -1 5 -3 W -IV	1500 watts, preset slide, 3-way, ivory	2	18 oz	
68151	D A P -1 5 -3 W -W H	1500 watts, preset slide, 3-way, white	2	18 oz	
68160	D A P -20-IV	2000 watts, preset slide, ivory	2	19 oz	
68161	D A P -20-W H	2000 watts, preset slide, white	2	19 oz	
68170	DAP-20-3W-IV	2000 watts, preset slide, 3-way, ivory	2	19 oz	
68171	DAP-20-3W-WH	2000 watts, preset slide, 3-way, white	2	19 oz	

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Luminist Series - Fluorescent (Electromagnetic Only)

Hunt Product Code	Model Number	Description	Unit Pack Master Carton	Unit Weight	NSN
120 volt					
68400	DAF-12-IV	12 lamps or 480 watts, preset slide, ivory	2	14 oz	
68401	DAF-12-WH	12 lamps or 480 watts, preset slide, white	2	14 oz	
68420	DAF-20-IV	20 lamps or 800 watts, preset slide, ivory	2	15 oz	
68421	DAF-20-WH	20 lamps or 800 watts, preset slide, white	2	15 oz	
68440	DAF-30-IV	30 lamps or 1200 watts, preset slide, ivory	2	18 oz	
68441	DAF-30-WH	30 lamps or 1200 watts, preset slide, white	2	18 oz	
68460	DAF-40-IV	40 lamps or 1600 watts, preset slide, ivory	2	22 oz	
68461	DAF-40-WH	40 lamps or 1600 watts, preset slide, white	2	22 oz	
277 Volt					
68410	DAF-12-7-IV	12 lamps or 480 watts, preset slide, ivory	2	14 oz	
68411	DAF-12-7-WH	12 lamps or 480 watts, preset slide, white	2	14 oz	
68430	DAF-20-7-IV	20 lamps or 800 watts, preset slide, ivory	2	15 oz	
68431	DAF-20-7-WH	20 lamps or 800 watts, preset slide, white	2	15 oz	
68450	DAF-30-7-IV	30 lamps or 1200 watts, preset slide, ivory	2	18 oz	
68451	DAF-30-7-WH	30 lamps or 1200 watts, preset slide, white	2	18 oz	
68470	DAF-40-7-IV	40 lamps or 1600 watts, preset slide, ivory	2	22 oz	
68471	DAF-40-7-WH	40 lamps or 1600 watts preset slide, white	2	22 oz	

Luminist Series - Low Voltage Incandescent (magnetic) - 120 Volt Applications

Hunt Product Code	M o d e l N u m b e r	D escription	U nit Pack Master Carton	Unit Weight	NSN
68300	D LV -IO -IV	1000 volt/amps, preset slide, ivory	2	16 oz	
68301	D LV -1 0 -W H	1000 volt/amps, preset slide, white	2	16 oz	
68310	D LV -1 0 -3 W -IV	1000 volt/amps, preset slide, 3-way, ivory	2	16 oz	
68311	D LV -1 0 -3 W -W H	1000 volt/amps, preset slide, 3-,vay, white	2	16 oz	
68320	D LV -1 5 -IV	1500 volt/amps, preset slide, ivory	2	22 oz	
68321	D LV -15-W H	1500 volt/amps, preset slide, white	2	22 oz	
68330	D LV -1 5 -3 W -IV	1500 volt/amps, preset slide, 3-way, ivory	2	22 oz	
68331	D LV -1 5 -3 W -W H	1500 volt/amps, preset slide, 3-way, white	2	22 oz	


HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Omega Series

- Applications: Incandescent.
- Slide-to-OFF switch.
- Calibrated slide control operates smoothly & accurately.
- Low-end trim adjustment.
- Wrap-around aluminum faceplate.
- No exposed fins or hardware.
- Limited one-year warranty.



Incandescent

Hunt Product Code	M o d e l N u m b e r	D e s c rip tio n	Unit Pack Master Carton	Unit Weight	NSN
120 Volt					
65130	S C -6-IV	600 watts, slide control, ivory	12	14 oz	
65006	S C -6-W H	600 watts, slide control, white	6	14 oz	
65131	S C -10-IV	1000 watts, slide control, ivory	6	15 oz	
65007	S C -10-W H	1000 watts, slide control, white	2	15 oz	
65132	S C -15-IV	1500 watts, slide control, ivory	1	18 oz	
65008	S C -15-W H	1500 watts, slide control, white	1	18 oz	
65133	S C -20-IV	2000 watts, slide control, ivory	1	19 oz	
65009	S C -20-W H	2000 watts, slide control, white	1	19 oz	
277 Volt					
65150	S C -647-IV	600 watts, slide control, ivory	1	12 oz	
65115	S C -647-W H	600 watts, slide control, white	1	12 oz	
65151	S C -1047-IV	1000 watts, slide control, ivory	1	15 oz	
65116	SC-1047-WH	1000 watts, slide control, white	1	15 oz	
65152	S C -2047-IV	2000 watts, slide control, ivory	1	18 oz	
65117	SC-2047-WH	2000 watts, slide control, white	1	18 oz	

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Revolution Series

- Applications: Incandescent & Fluorescent.
- Smooth action, full-range rotary switch.
- Snap-on plastic cover holds captive knob securely in place.
- Positive ON/OFF switch.
- Limited two-year warranty





Incandescent - 120 Volt applications

68200	ARD-8-IV	800 watts, captive rotary, ivory	1 0	14 oz	
68201	ARD-8-WH	800 watts, captive rotary, white	1 0	14 oz	
68210	ARD-8-3W-IV	800 watts, captive rotary, 3-way, ivory	2	14 oz	
68211	ARD-8-3W-WH	800 watts, captive rotary, 3-way, white	2	14 oz	
68220	ARD-10-IV	1000 watts, captive rotary, ivory	5	15 oz	
68221	ARD-10-WH	1000 watts, captive rotary, white	5	15 oz	
68230	ARD-10-3W-IV	1000 watts, captive rotary, 3-way, ivory	2	15 oz	
68231	ARD-10-3W-WH	1000 watts, captive rotary, 3-way, white	2	15 oz	
68240	ARD-15-IV	1500 watts, captive rotary, ivory	2	18 oz	
68241	ARD-15-WH	1500 watts, captive rotary, white	2	18 oz	
68250	ARD-20-IV	2000 watts, captive rotary, ivory	2	19 oz	
68251	ARD-20-WH	2000 watts, captive rotary, white	2	19 oz	

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





A-Line Series

- Applications: Incandescent, Fluorescent, Low Voltage, & Fan-Speed Control
- Smooth action, full-range rotary switch.
- Decorative black, snap-in bezel.
- Economical, dependable dimming solution.
- Positive ON/OFF switch.
- Limited one-year warranty

Incandescent



Hunt Product Code	Model Number	Description	U n it Pack M aster C arton	Unit Weight	NSN
120 Volt					
65040	A-600	600 watts, rotary	12	10 oz	
65041	A -600-3W	600 watts, rotary, 3-way, tap ON/OFF	6	10 oz	
65042	A -1000	1000 watts, rotary	6	11 oz	
65043	A P S -1000-3W	1000 watts, rotary, 3-way, tap ON/OFF	1	15 oz	
65044	A - 1500	1500 watts, rotary	1	16 oz	
65045	A P S -1500-3W	1500 watts, rotary, 3-way, tap ON/OFF	1	18 oz	
65046	A -2000	2000 watts, rotary	1	19 oz	
277 Volt					
65060	A -6 4 7	600 watts, rotary	1	10 oz	
65061	A -1 0 4 7	1000 watts, rotary	1	11 oz	
65062	A -2 0 4 7	2000 watts, rotary	1	19 oz	

A-Line Series - Low Voltage Incandescent

H u n t P ro d u c t C o d e	M o d e l N u m b e r	D e s c rip tio n	U nit Pack Master Carton	Unit Weight	NSN
120 Volt					
65070	A LV -6	600 volt/amps, rotary	1	10 oz	
65071	A LV -1 0	1 000 volt/amps, rotary	1	11 oz	
65072	A LV -1 5	1500 volt/amps, rotary	1	16 oz	
65073	A LV -2 0	2000 volt/amps, rotary	1	17 oz	
277 Volt					
65113	A LV -6 4 7	600 volt/amps, rotary	1	12 oz	
65114	A LV -1 0 4 7	1 000 volt/amps, rotary	1	14 oz	
65118	A LV -2 0 4 7	2000 volt/amps, rotary	1	16 oz	

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Modular Dimming Systems

Incandescent & Fluorescent (Electromagnetic Only)

Hunt Product Code	Model Number	Description	NSN
Modular D	imming Control Switche	es Eclipsis Series	
71310	PS-IFC-1-IV	Preset Slide, Controls ID or FD series modular unit, Ivory	
71311	PS-IFC-1-Wh	Preset slide, Controls ID or FD series modular unit White	
71315	PS-IFC-1-3W-IV	Preset slide 3 wayControls ID or FD series modular unit, Ivory	
71316	PS-IFC-1-3W-WH	Preset slide 3 way,Controls ID or FD series modular unit White	
Incandesce	ent - 120 Volt	•	
65384	ID-30-F Master	3kw, 24 amp Master unit	
65385	ID-30-SF Slave	3kw, 24 amp Slave unit	
65386	ID-20-F Master	2kw, 16 amp Master unit	
65387	ID-20-SF Slave	2kw, 16 amp Slave unit	
Fluorescen	ıt - 120 Volt (electromaç	gnetic)	
65402	FD-30 Master	Master unit for up to (56) F-40 lamps with up to (7) Slaves	
65403	FD-30 S Slave	Slave unit for up to (56) F-40 lamps	
65404	FD-20 Master	Master unit for up to (38) F-40 lamps with up to (7) Slaves	
65405	FD-20 S Slave	Slave unit for up to (38) F-40 lamps	
Fluorescen	t - 277 Volt (electromaç	gnetic)	
65410	FD-27 Master	Master unit for up to (40) F-40 lamps with up to (7) Slaves	
65411	FD-27 S Slave	Slave unit for up to (40) F-40 lamps	

HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.





Architectural Dimming Systems

HUNT manufactures easy-to-understand, simple-to-use, economical solutions to high power dimming needs. Controlled lighting includes: Incandescent, Fluorescent, Low-Voltage, Neon and Cold Cathode light sources, as well as, Fan-Speed and Motor Control loads. Custom 50 Hz and 60 Hz available.

For additional information on the following listed controls contact the DSCP Lighting Team.

PR-4 Preset Dimming Control Panel

Designed To Accommodate Diversified Lighting Control Requirements.


- Control 4 to 15 zones of lighting from full OFF to full ON in four different scenes. Each scene may be randomly accessed.
- 7 models meet virtually any lighting control application.
- Zone lighting managed by easy to operate slide controls.
- Four illuminated scene select switches provide easy readability.
- Optional remotes override presets and bring lighting to full brightness levels.
- Single fade rate control for all zones and all scenes adjustable from 0 to 60 seconds.
- Low -Voltage control
- Truly Distinctive Styling
- Elegant, brushed aluminum design with no visible screws.
- Transparent security door panel allows viewing of lighted slide controls inside of door.

Door is magnetically latched and supported by hinges which are not visible when door is closed.

H-Series Dimming Control Panel

A simple and economical alternative for lighting control.

- Crisp, professional appearance.
- Anodized, brushed aluminum finish with black engraving (custom colors and engraving available)
- Long 60 mm slide potentiometers simplify use.
- Flush mounted.
- Variety of models accommodate most dimming needs.



HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.









Prewired Dimming Panels

HUNT's Simplicity series prewired dimming panels offer the most cost effective solution to high-power dimming needs. These panels are easy-to-install, and available in either surface or recessed-mounted styles accommodating up to 36 U.L. Listed dimmers with a maximum load of 72 Kw. The panels control Incandescent, Fluorescent, Low Voltage, Neon, Fan Speed Controls or non-dimmed loads.

Features include:

- Dimmers prewired to terminal blocks.
- Thermostatically controlled fans.
- Air cooling vents.
- Engraved identification plates.
- Hinged door on recessed unit.
- Available with up to 36 dimmers
- UL Listed
- NEMA enclosure

Available options Circuit breakers and locking doors



HUNT Dimming is proud to be an EPA EnergyStar® Buildings Ally.



